

## DOUBLE BOND™

**MFM Building Products Corp.** manufactures a wide range of innovative waterproofing products for the building industry. Proven through many years of use in the field, MFM products are engineered for superior performance and ease of installation.

MFM DoubleBond™ is designed for sealing applications requiring an adhesive surface on both sides. MFM DoubleBond™ can be used as a self-sealing gasket replacing messy caulks and is ideal around skylights, windows and vents.

### DESCRIPTION

Pressure sensitive MFM DoubleBond™ is a non-reinforced 35-mil adhesive tape. MFM DoubleBond™ adheres aggressively to most smooth surfaces including plywood. It self-seals around nails and provides a dependable waterproofing barrier over a wide range of weather conditions. The product is composed of a rubberized asphalt compound with release paper on one side and release film on the other. Use DoubleBond™ for light-duty applications where a high degree of conformability is desired and both sides must be adhesive.

### APPLICATION

MFM DoubleBond™ must be protected from harmful UV light by the use of a protective covering. Use DoubleBond™

only in situations where it will be protected from direct exposure to sunlight or other UV sources.

1) DoubleBond™ is designed to have the release paper removed as you are applying it to the surface. The blue release film should not be removed until immediately before you will be applying to the tape.

2) Apply MFM DoubleBond™ at ambient temperatures above 50° F. At lower temperatures, use MFM Spray Adhesive.

3) The surface to which MFM DoubleBond™ is to be adhered to should be clean, dry, smooth and free of contaminants. Use a wire brush and primer as necessary to ensure such a surface. Masonry surfaces must be primed with MFM Prime-A-Seal.

4) Carefully align roll, peel back 12 inches of release paper and press exposed portion into place.

5) Carefully unroll MFM DoubleBond™, removing paper and pressing material into place as you go.

6) Repeat with next section.

7) The blue release film should not be removed until the moment you are ready to adhere to the tape. Never leave DoubleBond™ uncovered once the release film has been removed. If the film has not been removed, do not leave

DoubleBond™ uncovered for more than 8 hours.

### SPECIAL INSTRUCTIONS

1) Always cover DoubleBond™ as the tape is not designed for prolonged exposure to direct sunlight.

2) Store DoubleBond™ in the carton and remove only as needed.

3) Store carton on end in a dry place at temperatures not exceeding 100° F.

4) If additional adhesion is required, use MFM Spray Adhesive.

### CAUTION

The adhesive in MFM DoubleBond™ is incompatible with EPDM rubber. Never apply MFM DoubleBond™ to such a surface.

### TECHNICAL DATA

PROPERTY	Result
Thickness	35 mils min.
Color	Black
Roll Length	50'
Roll Width	4", 6"
Rolls/Carton	4" = 9, 6" = 6
Carton Weight	36 lbs
Area/Carton	150 ft <sup>2</sup>