

MFM Whisper Spray

Brush- or Spray-applied Contact Cement

MFM Building Products Corp. manufactures a wide range of innovative waterproofing products for the building industry. Proven through many years of use in the field, MFM products are engineered for superior performance and ease of installation.

DESCRIPTION

MFM Whisper Spray is a synthetic, elastomeric-based brush- or spray-applied contact cement tested for use with all MFM self-adhering products. Use of Whisper Spray will greatly enhance adhesive properties of MFM self-adhering products and extend the application temperature range.

Ideal for use with MFM WindowWrap™, Peel & Seal™, FlexClad-400™, Post & Pole™, SubSeal-40™, SubSeal-60™, and Enkadri & Drain™ BTM.

May be used with foam, fabrics, wood, metals, plasterboard, fiberglass, masonry, and most construction materials.

BENEFITS

- Good heat resistance
- High solids
- Non ozone depleting
- Semi-pressure sensitive
- HAPS free

WARNINGS

- **Whisper Spray is highly flammable!**
- Consult Material Safety Data Sheet prior to use.
- **Store away from direct sunlight! Do not store above 115°F!**
- Keep container closed when not in use.
- **Container may contain residual adhesive and/or solvents. Dispose of empty containers in accordance with applicable local, county, state, and federal regulations.**

SPRAY EQUIPMENT

Apply with a Binks 2001 or 95 gun #63B or 66 nozzle DeVilbiss JGA503 gun #E, FF or FX nozzle or comparable spray equipment.

APPLICATION

1. Apply only to surface area to which MFM product is going to be immediately applied.
2. Substrate should be clean & dry.
3. Brush or spray Whisper Spray in a light, even coating to the substrate.
4. Do not apply Whisper Spray directly to the MFM self-adhering membrane!
5. Avoid excessive adhesive buildup or bubbles on the substrate.
6. Before applying the membrane, allow Whisper Spray to cure for a minimum 60 seconds, depending upon temperature, humidity and wind conditions, or until the surface of the adhesive no longer appears or feels "wet".
7. Check substrate for proper curing. When the Whisper Spray coating no longer appears or feels "wet" apply the membrane over the substrate and apply even pressure with a hand roller to the entire surface.
8. Monitor the adhesion as you go. Stop installation if the membrane is not adhering properly.

WHISPER SPRAY MUST CURE BRIEFLY SO THAT SOLVENTS MAY EVAPORATE BEFORE MEMBRANE IS APPLIED!

TECHNICAL DATA

Bonding time	10 – 20 minutes
Coverage	Approx 150 sq. ft. /gal.
Application Range	25° F to 90° F
Color	Amber
Total Solids	28%
Viscosity	110cps @ 77 sp #2, 30 RPM
Weight	6.6 lbs. / gal.
Packaging	5 gallon pail

To obtain a Material Safety Data Sheet, contact MFM Building Products, 1-800-882-7663.