



MFM Building Products Corp. manufactures a wide range of innovative waterproofing products for the building industry. Proven through many years of use in the field, MFM products are engineered for superior performance and ease of installation.

DESCRIPTION

WindowWrap™ PSX-20 is a self-adhering, self-sealing waterproofing tape designed for use around windows, doors, building seams and in general construction. It is composed of a silver polymer film that is coated with an aggressive Broad Temperature Spectrum (BTS™) asphalt adhesive. A release liner protects the adhesive and is removed as the tape is installed.

The BTS™ adhesive self-seals around punctures such as nails and staples. This advanced system bonds to all common building and window materials and seals around fasteners to prevent damage caused by water penetration.

SPECIAL FEATURES

WindowWrap™ PSX-20 offers the contractor and property owner these extra features:

- Proven and patented, silver polymer construction resists exposure to ultraviolet rays.
- Aggressive Broad Temperature Spectrum (BTS) adhesive sticks to all common building materials and remains flexible at low temperatures.
- Adheres to prepared substrates of plywood, OSB, masonry, aluminum, vinyl, steel, drywall, insulation board, and house wrap.
- Prevents water, air, insect, and noise infiltration. Helps to prevent mold and mildew.
- Easy-to-remove release liner.
- Uniform thickness for dependable protection.
- Self-seals around fasteners including nails and staples.

- Eliminates Leaks – multiple layers of protection seal out water.
- BTS adhesive won't crack or dry out (when properly installed).
- May be left exposed for 180 days.

INTENDED USES

Install on the window sill to protect against moisture that can contribute to rot, mold and mildew. Use to seal the window flange to the building wall in new construction to prevent window leaks, seal around doors, under siding, exterior plaster, sill plates and wall joints, or in any application where the membrane is protected from long-term ultraviolet exposure.


Application Range	>35°F
Color	Silver
Roll Length	100ft
Roll Width	3" 4" 6" 9" 12" 18" 36"
Carton Weight	55lbs Nom.
Area / Carton	300ft²
Maximum Temp.	170°F

FIVE YEAR LIMITED WARRANTY


MFM Building Products Corp. (MFM) warrants materials to be free from leaks caused by defects in material or manufacturing for a period of five (5) years from the date of purchase when applied according to published directions and will, at its option, resupply or refund the purchase price of any materials proven to be defective. Misapplication or poor workmanship is specifically excluded under the terms of this warranty. MFM shall be liable for no additional remedies, hereby expressly denying any other claims for damages, whether direct or indirect, consequential or incidental, including but not limited to property damage, personal injury to the buyer or to a third party and loss of business or profit arising from the use or inability to use the product. Any implied warranties arising under state law are limited to the duration and terms of this express warranty.

PROPERTY	TEST METHOD	RESULTS
Thickness	ASTM D 1970	25 mils Nom.
Pliability @ 0°F	AAMA 711	Pass
Nail Sealability	ASTM D 1970	Pass
Tensile MD	ASTM D 1970	16 lbf/in
Tensile CMD	ASTM D 1970	21 lbf/in
Elongation MD	ASTM D 1970	44 %
Elongation CMD	ASTM D 1970	60 %


For detailed instructions see ASI - WW publication or original carton.




Step 1 Install sill



Step 2 Install window



Step 3 Install sides



Step 4 Install header

WindowWrap is protected by U.S. patent No. 6,479,119